



**Confidentiality Disclaimer:**

This document and the technology disclosed thereby is owned by Argent International, Inc. It contains confidential proprietary and/or trade secret information and must not be copied. The document and the information it contains must be used only by the recipient for the specific use for which it was requested. This document and all copies of it must be returned immediately upon the request to do so by Argent International, Inc

**APPLICATION DATA SHEET**

**Note:** If more information is needed please call for a technical data sheet.

**PRODUCT: SJ3572 (Nylon Hook)**

**PRODUCT DESCRIPTION:** 3M™ Scotchmate™ Reclosable Fasteners offer advanced closure alternatives to zippers, screws, snaps, hooks and more. They offer greater design flexibility, faster product assembly, smoother and cleaner exterior surfaces and improved product performance in many applications.

**PRODUCT CONSTRUCTION:**

Fastener Products	Scotchmate SJ3572 (Hook)
	Hook - Nylon 6 hook, Nylon 6.6 weave
	Adhesive - Acrylic
Thickness <sup>b</sup> max. unmated	3/32" (2.4 mm)
Liner	Clear Polypropylene Film

**TYPICAL CLOSURE AND SYSTEM PERFORMANCE PHYSICAL PROPERTIES & PERFORMANCE CHARACTERISTICS:**

<b>Scotchmate SJ3571 Loop Engaged to Scotchmate SJ3572 Hook</b>		
<b>Static Tensile Holding Power</b>	158°F	100 minutes
	200°F	100 minutes
	100°F/100% RH	100 minutes
<b>Peel</b>		
Peel Strength (90° Peel, Flexible to Rigid)	1.8 (313.2)	
<b>Engaged Thickness<sup>c</sup></b>	0.10 (2.5) to 0.21 (5.3) ± 15%	

**FLAMMABILITY RESISTANCE:** Scotchmate SJ3571/72 meet the requirements of FMVSS-302 when attached to a thin metal panel. Scotchmate's SJ3571/72 adhesive has been formulated to withstand typical outdoor temperature, humidity and ultraviolet exposure conditions.

**Notice:** All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.