



Confidentiality Disclaimer:

This document and the technology disclosed thereby is owned by Argent International, Inc. It contains confidential proprietary and/or trade secret information and must not be copied. The document and the information it contains must be used only by the recipient for the specific use for which it was requested. This document and all copies of it must be returned immediately upon the request to do so by Argent International, Inc

APPLICATION DATA SHEET

Note: If more information is needed please call for a technical data sheet.

PRODUCT: wirestrap™ Self Adhesive Wire Fastener

PRODUCT DESCRIPTION: Designed to be used as a wire, cable, or lightweight tubing fastener. WireStrap's adhesive system has excellent resistance to water, solvents, oils, U.V. light and moderately high temperatures. The supporting strap is constructed of flexible polyethylene film. WireStrap's can be pre-applied to wire harnesses or installed at assembly. U.S. Patent #'s 5,827,589 & 6,631,335.

TECHNICAL DATA:

Strap Material:	Low Density Polyethylene
Adhesive:	3M 9672LE *
Tensile Strength (film):	3.0 N/mm
Peel Adhesion / Stainless Steel:	140 Oz. / In.
Service Temperature:	-40°F to 200°F
Application Temperature:	40° to 120°F

* Several other adhesive systems are available to meet specific application requirements.

Notice: All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.