



APPLICATION DATA SHEET

ARV0108 - Wool Felt Tape

PRODUCT DESCRIPTION: ARV0108 wool felt tape is designed to be used for BSR (buzz, squeak, and rattle) applications that require both anti-squeak and anti-rattle capabilities. This 75% wool felt composite meets SAE commercial standard grade specifications and performs well in applications that can also benefit from sound dampening and abrasion resistance. ARV0108 utilizes a low VOC, high performance modified acrylic adhesive system with wool felt which provides excellent adhesion to most substrates, including low surface energy plastics as well as many types of foam. The high-performance of ARV0108 makes it an excellent choice for a variety of BSR applications in the interior of vehicles such as IP clusters, headliners, center consoles and more.

VALUES:

Construction:	Low VOC adhesive, wool felt
Abrasion Resistance:	Good
Flammability:	FMVSS 302
Thickness:	Various thickness available: 1/16 to 3/32
Temperature	-40°C to 120°C
Bond Peel Test: 75°F +/- 5°	25 N/25mm

Notice: All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.