



APPLICATION DATA SHEET

ARV3200 – Flock Tape

PRODUCT DESCRIPTION: Flock tape excels in applications that require abrasion resistance and moderate sound dampening. Flock tape’s dense nylon fibers form a cushion between mating components and resist crushing to effectively stop most squeak and rattle challenges. Our flock tape utilizes an OEM tested and approved, high-performance adhesive system, which provides excellent adhesion to most substrates. Its high-performance and low cost make it an excellent choice for a variety of BSR applications.

PROPERTIES:	VALUES:
Construction:	100% Nylon, Black
Abrasion Resistance, 500 Cycles, CS-10, 1kg load (Type 1)	Wet (CS-10/500g): 1000 Cycles Dry (CS-10/1000g): 1500 Cycles
Flammability:	FMVSS 302 (Flock Only)
Thickness:	1.0mm thick +/- 15%
Temperature Range:	-40° C to 120° C
	ABS: PP:
Bond Peel Test - Original	8.9 lbs/in 4.0 lbs/in
Bond Peel Test - 7d @ 79° C	7.5 lbs/in 6.4 lbs/in

*When testing for flammability, all adhesive backed tapes must be tested applied to the mating substrate. Flammability testing, unless otherwise specified or agreed upon, is the responsibility of the component supplier.

Notice: All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.