Confidentiality Disclaimer:

This document and the technology disclosed thereby is owned by Argent International, Inc. It contains confidential proprietary and/or trade secret information and must not be copied. The document and the information it contains must be used only by the recipient for the specific use for which it was requested. This document and all copies of it must be returned immediately upon the request to do so by Argent International, Inc

APPLICATION DATA SHEET

Note: If more information is needed please call for a technical data sheet.

PRODUCT: ARV9849 - Polyester Film Tape

PRODUCT DESCRIPTION: 3M™ Polyester Film Tape has excellent tensile strength and ab rasion resistance that can be used for many permanent edging and reinforcing types of applications.

PRODUCT CONSTRUCTION:

Backing	Adhesive
Polyester	Acrylic

TYPICAL PHYSICAL PROPERTIES:

Adhesion to Steel:	42 oz./in/ width (46 N/100 mm)
Tensile Strength:	120 lbs./in. width (2100 N/100 mm)
Temperature Use:	Dimensionally stable over temperature range from -60° to 300°F (-50° to 149°C)

FEATURES:

- Polyester backing provides puncture resistance.
- Long aging acrylic adhesive to help reduce failures often cau sed by adhesive degradation.

Notice: All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions con cerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.

Argent International, Inc. • 41016 Concept Drive • Pl ymouth, Michigan • 48170
Phone: (800) 223-9890 • Fax: (734) 582-9999 • www.arg ent-international.com