

**Confidentiality Disclaimer:**

This document and the technology disclosed thereby is owned by Argent International, Inc.. It contains confidential proprietary and/ or trade secret information and must not be copied. The document and the information it contains must be used only by the recipient for the specific use for which it was requested. This document and all copies of it must be returned immediately upon request to do so by Argent International, Inc.

**APPLICATION DATA SHEET****PRODUCT: Restricted Flow**

<b>Test</b>	<b>Minimum</b>	<b>Maximum</b>	<b>Results</b>	<b>Units</b>
Density	1.7		1.95	lbs/ft3
Tensile Strength	10		15.5	psi
Elongation	125		204	%
Tear Strength	1		1.7	lbs/in
50% CFD (Original)	0.18	0.62	0.47	psi
50% CFD (Heat Aged)		10	6	%
50% CFD (Autoclaved)		15	2	%
50% Compression Set		15	2	%
Odor		No Offensive Odor	No Offensive Odor	-
Low Temperature Flexibility	No Rupture		No Rupture	-
Low Temp Flex (Heat Aged)	No Rupture		No Rupture	-
Air Flow	1.5		2	psi
Flammability		4	0	in/min

**Notice:** All statements, information and data given herein are believed to be accurate and reliable. These values are intended as guides only and not as specification limits. This data is presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may or may not be required.